



RM Series Compact, Rugged & Durable

Analog UHF 2 Watt

RMU2040

- 2 Watt transmit power
- UHF provides coverage up to 250,000 sq. ft. or 20 floors
- 2 channels standard (expands up to 4)
- Channel scan
- 99 built-in UHF Frequencies; 12.5 kHz narrowband compliant
- Interference Eliminator with 219 PL/DPL codes, including 6 customizable codes
- Audio accessory jack for use with earpieces and headsets
- Channel Announcement
- Meet Military 810 C, D, E, F, G and IP54/55 specifications for high resistance to dust, moisture, shock and vibration
- Antimicrobial Protection
- 2 programmable buttons for quick one-touch access to features
- Voice assisted programming
- Single-unit drop-in charger provides charging and battery level status via tri-color LED
- Easy Cloning with Single-Unit Charger Cloning Cable or Multi-Unit Charger (sold separately)
- Weighs 8.6 ounces with battery

INCLUDES:

- RMU2040 radio
- 2100 mAh 3.7V Lithium Ion Rechargeable Battery for up to 15 hours of battery life
- 10 Hr Drop-In Charging Tray w/ Wall Adaptor
- Swivel Holster with 3.5" Belt Clip



Dimensions: 4.5"H x 2.25"W x 1.5"D, Weight w/ Battery 8.6 oz., Color: Black

Model No.	Band	Transmit Power	No. of Channels	Range and Coverage	MSRP	1 - 5	6 - 11	12+
RMU2040	UHF	2 Watt	2 (expands up to 4)	Up to 250,000 sq. ft. or 20 floors	\$245	\$179	\$170	\$161



RM Series Compact, Rugged & Durable **Analog UHF 2 Watt**

RMU2080

- 2 Watt transmit power
- UHF provides coverage up to 250,000 sq. ft. or 20 floors
- 8 Channels
- Channel scan
- 99 built-in UHF Frequencies; 12.5 kHz narrowband compliant
- NOAA Weather Radio with Alerts
- Audio accessory jack for use with earpieces and headsets
- Channel Announcement
- Meet Military 810 C, D, E, F, G and IP54/55 specifications for high resistance to dust, moisture, shock and vibration
- Antimicrobial Protection
- 2 programmable buttons for quick one-touch access to features
- Voice assisted programming
- Single-unit drop-in charger provides charging and battery level status via tri-color LED
- Easy Cloning with Single-Unit Charger Cloning Cable or Multi-Unit Charger (sold separately)
- Weighs 8.6 ounces with battery

INCLUDES:

- RMU2080 radio
- 2100 mAh 3.7V Lithium Ion Rechargeable Battery for up to 15 hours of battery life
- 10 Hr Drop-In Charging Tray w/ Wall Adaptor
- Swivel Holster with 3.5" Belt Clip



Dimensions: 4.5"H x 2.25"W x 1.5"D, Weight w/ Battery 8.6 oz, Color: Black

Model No.	Band	Transmit Power	No. of Channels	Range and Coverage	MSRP	1 - 5	6 - 11	12+
RMU2080	UHF	2 Watt	8	Up to 250,000 sq. ft. or 20 floors	\$290	\$209	\$199	\$189



RM Series Compact, Rugged & Durable

Analog UHF 2 Watt

RMU2080d

- 2 Watt transmit power
- UHF provides coverage up to 250,000 sq. ft. or 20 floors
- 8 Channels
- Channel scan
- 99 built-in UHF Frequencies; 12.5 kHz narrowband compliant
- LCD Display shows channel or workgroup; provides quick access to frequency, code settings and battery status
- Interference Eliminator with 219 PL/DPL codes, including 6 customizable codes
- NOAA Weather Radio with Alerts
- Audio accessory jack for use with earpieces and headsets
- Channel Announcement
- Meet Military 810 C, D, E, F, G and IP54/55 specifications for high resistance to dust, moisture, shock and vibration
- Antimicrobial Protection
- 2 programmable buttons for quick one-touch access to features
- Voice assisted programming
- Single-unit drop-in charger provides charging and battery level status via tri-color LED
- Easy Cloning with Single-Unit Charger Cloning Cable or Multi-Unit Charger (sold separately)
- Weighs 8.6 ounces with battery

INCLUDES:

- RMU2080d radio
- 2100 mAh 3.7V Lithium Ion Rechargeable Battery for up to 15 hours of battery life
- 10 Hr Drop-In Charging Tray w/ Wall Adaptor
- Swivel Belt Holster with 3.5" Spring Clip



Dimensions: 4.5"H x 2.25"W x 1.5"D, Weight w/ Battery 8.6 oz, Color: Black

Model No.	Band	Transmit Power	No. of Channels	Range and Coverage	MSRP	1 - 5	6 - 11	12+
RMU2080d	UHF	2 Watt	8	Up to 250,000 sq. ft. or 20 floors	\$310	\$219	\$208	\$198



RM Series Compact, Rugged & Durable

Analog VHF 2 Watt

RMV2080

- 2 Watt transmit power
- VHF provides coverage up to 200,000 sq. ft. or 10 floors
- 8 Channels
- Channel scan
- 27 Selectable VHF Frequencies; 12.5 kHz narrowband compliant
- NOAA Weather Radio with Alerts
- Audio accessory jack for use with earpieces and headsets
- Channel Announcement
- Meet Military 810 C, D, E, F, G and IP54/55 specifications for high resistance to dust, moisture, shock and vibration
- Antimicrobial Protection
- 2 programmable buttons for quick one-touch access to features
- Voice assisted programming
- Single-unit drop-in charger provides charging and battery level status via tri-color LED
- Easy Cloning with Single-Unit Charger Cloning Cable or Multi-Unit Charger (sold separately)
- Weighs 8.6 ounces with battery

INCLUDES:

- RMV2080 radio
- 2100 mAh 3.7V Lithium Ion Rechargeable Battery for up to 15 hours of battery life
- 10 Hr Drop-In Charging Tray w/ Wall Adaptor
- Swivel Belt Holster with 3.5" Spring Clip



Dimensions: 4.5"H x 2.25"W x 1.5"D, Weight w/ Battery 8.6 oz, Color: Black

Model No.	Band	Transmit Power	No. of Channels	Range and Coverage	MSRP	1 - 5	6 - 11	12+
RMV2080	VHF	2 Watt	8	Up to 200,000 sq. ft. or 10 floors	\$245	\$174	\$165	\$157

Key Accessories



PMNN4434

Lithium Ion Battery

COST

\$39



PMLN6394

Single-Unit Charger

\$22



PMLN6384

Multi-Unit Charger

\$159



HKLN4510

Swivel Holster

COST

\$12



HKKN4027

CPS Cable

\$25



HKKN4028

RM Cloning Cable

\$12