

# Calbrite™

## Stainless Steel Conduit Systems

### Stainless Steel Bare Flex Conduit

#### Features:

- Excellent strength and durability
- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance & aesthetic appearance
- Extremely flexible with smooth interior ease of installation and wire pull thru
- Compatible with Calbrite™ stainless steel flex connectors & 90's
- Interlock (double buckle) style
- Manufactured in 25' coils




#### Certifications and Compliances:

Calbrite™ stainless steel bare flex is manufactured in compliance with UL514B and ANSI standards. Manufactured in the US.

#### Applications:


Flexible stainless steel conduit can be used for protecting electronic and electrical wires, and cable. Suitable for corrosive environments, including pumps, motors, HVAC systems, machine tools, electrical housings, and cabinetry. Good absorption of motion and vibration.



Double Buckle

#### Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments



Trade Size	Part Number	Outside Diameter	Inside Diameter	Bend Radius	Weight per 25' Coil (lbs.)
1/2"	S60500CTFX	0.744"	0.610"	4"	4.50
3/4"	S60700CTFX	0.960"	0.790"	4-1/2"	5.50
1"	S61000CTFX	1.160"	1.010"	6"	7.00
1-1/4"	S61200CTFX	1.500"	1.330"	7-1/2"	8.50
1-1/2"	S61500CTFX	1.750"	1.520"	9"	10.00
2"	S62000CTFX	2.125"	2.020"	10"	13.00

All dimensions are for informational purposes only \* Tolerances +/- 5%