



PRODUCT DATA SHEET

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

PART NUMBER: 97272
DESCRIPTION: 23 AWG /4 Pair Riser CATEGORY 6 DATA CABLE
COMPLIANCE:

- ETL Listed Type CMR or CMX OUTDOOR to UL Standard 444
- C(UL) listed CMG FT4
- ETL Verified to TIA/EIA 568C.2-1
- Meets or exceeds TIA/EIA 568C.2-1

APPLICATION: Utilizes a small round filler design providing a smaller diameter and greater flexibility for easier handling.
 Lead free jacket.

Construction Parameters:

		<u>DIAMETER*</u>
Conductor	23 AWG Solid Bare Copper	0.023
Dielectric	Solid FRPE	0.042
Assembly	Each pair has different lay length for cross-talk prevention and ripcord added.	
Jacket	PVC	0.207

* = Nominal value

Product Electrical Characteristics:

Freq (MHZ)	Attn. (dB/100m) Max	Next Loss (dB) Min	PSNEXT Loss (dB) Min	ACR (Db@100m) Min	PSACR (dB@100m) Min	ELFEXT (dB@100m) Min	PS-ELFEXT (dB@100m) Min	Ret. Loss (dB)	
1	2	74.3	72.3	72.3	70.3	67.8	64.8	20.0	Mutual Capacitance (nf / 100m) Nominal
10	6	59.3	57.3	53.3	51.3	47.8	44.8	25.0	4.4
16	7.6	56.2	54.2	48.6	46.6	43.7	40.7	25.0	DC Resistance (Ohms / 100 m) Maximum
20	8.5	54.8	52.8	46.3	44.3	41.8	38.8	25.0	8.9
31.25	10.7	51.9	49.9	41.2	39.2	37.9	34.9	23.6	Delay Skew (ns / 100 m) Maximum
62.5	15.4	47.4	45.4	32.0	30.0	31.9	28.9	21.5	25
100	19.8	44.3	42.3	24.5	22.5	27.8	24.8	20.1	Velocity of Prop. (1%):
200	29.0	39.8	37.8	10.8	8.8	21.8	18.8	18.0	70
250	32.8	38.3	36.3	5.5	3.5	19.8	16.8	17.3	Input Impedance (Ohms @ 1-100 Mhz)
350	40.0	36.2	34.2	-----	-----	16.9	13.9	16.3	100+/-15
400	43.2	35.3	33.3	-----	-----	15.7	12.7	15.9	100+/-32

Pair Colors: W/BL with BL, W/OR with O, W/GR with GR, W/BR with BR
Jacket Color: Standard colors are Blue and Gray

Legend (Ink Print) CAT6 COLEMAN CABLE 97272 CAT6 23 AWG 4PR UTP C(ETL)US LISTED 2003548 TYPE CMX-OUTDOOR OR CMR FT4 ETL VERIFIED TO TIA/EIA-568-C.2 CATEGORY 6
(Also printed with sequential footage & date code)

This product complies with European Directive 2002/95/EC (RoHS)
 On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____

Customer Approval _____

Specification Issue Date: August 13, 2010