

# TAPPAN™



A Southwire Company

100 Bradley Parkway • Blauvelt, NY 10913  
Phone: 1-800-WIRE-911 • Fax: 1-845-353-9315

## SPECIFICATION SHEET

**TAPPAN Spec. P20032.1**

Update 1.3 5/4/2012

2C 22 AWG SHIELDED COMMERCIAL AUDIO AND GENERAL PURPOSE  
LOW VOLTAGE POWER LIMITED CABLE 75C 300V PLENUM RATED

CONSTRUCTION: 22 AWG 7 STRAND BARE COPPER 2 CONDUCTORS TWISTED  
INSULATION: LS-PVC  
COLOR CODE: BLACK, RED  
SHIELD/DRAIN: ALUMINUM/POLYESTER FOIL (OUT); 24AWG 7 STRAND TINNED COPPER DRAIN  
ASSEMBLY: 2 CONDUCTORS TWISTED, SHIELDED AND JACKETED  
JACKET: LS-PVC WHITE (OTHER COLORS AVAILABLE; MOQ MAY APPLY)  
DIAMETER: 0.118" Nominal  
CABLE WT: 11 Lbs/1000Ft Approx (Net Weight)  
PRINT LEGEND: E118871 CMP/CL3P/FPLP 22AWG (UL) c(UL) MADE IN USA RoHS COMPLIANT  
NEC: CMP/CL3P/FPLP  
FOR RISER RATED VERSION GO TO SPEC. NO. R20007  
COMPLIANCE: UL 444 CMP by (UL) / NEC ARTICLE 800 / CSA C22.2 by c(UL) / RoHS  
FLAME TEST: NFPA 262(UL 910) / CSA FT6  
CAPACITANCE: 39.7 pF/ft Nominal  
VEL OF PROP: 55%  
IMPEDANCE: 47 OHMS  
RESISTANCE: 17.5 OHMS D.C. PER 1000 FT @ 68 DEG. F Maximum  
TEMP/VOLTAGE: 75C / 300V  
MISC: MADE IN USA  
TAPPAN PART No: 2280AB2M/CMP/CL3P

\* +/- 10% Manufacturing tolerance

\* On non-standard product, customer agrees to accept all lengths manufactured



Tappan Wire & Cable Inc. provides information and specifications on an "as is" basis. Information in specifications described herein are subject to error and/or omission, and subject to change without notice. Although we make all efforts possible to ensure the accuracy and timeliness of the information, Tappan Wire & Cable, will not be held liable for any damages whatsoever, even if advised of the possibility of such damages, arising from the use, or inability to use, the information or specifications herein. Please refer to our "Website Use Policy", listed on our website, [www.tappanwire.com](http://www.tappanwire.com), under the Sales Support Section for full details, or contact your Tappan Representative. This drawing may contain patented or proprietary information. It is the property of Tappan Wire and must not be used in any way detrimental to Tappan Wire. Acceptance by signature of this drawing will be considered as an agreement of and acceptance of the foregoing.