

2P





ENR Value Series Dead Front Interlocked Circuit Breaking Receptacles

ENP Plugs

Cl. I, Div. 1 & 2, Groups B†, C, D
 Cl. II, Div. 1 & 2, Groups F, G
 Cl. III
 NEMA 3, 7BCD, 9FG, 12

Explosionproof
 Dust-Ignitionproof
 Raintight
 Wet Locations

Ordering Information:

									
15 A	15 A Receptacle Rating	Description	Hub Size	Single Gang* Receptacle Assembly Cat. #	Two Gang** Receptacle Assembly Cat. #	Receptacle† Unit Only Cat. #	NEMA Config.	15 A Plug‡ Cat. #	NEMA Config.
CSA	15 Amp 125 Volt	Dead End	1/2"	ENR11151	ENR12151	ENR5151	5-15R	ENP5151	5-15P
			3/4"	ENR21151	ENR22151				
		Through Feed	1"	ENR31151	ENR32151				
			1/2"	ENRC11151	ENRC12151				
				3/4"	ENRC21151	ENRC22151			
				1"	ENRC31151	ENRC32151			
UL	15 Amp 250 Volt	Dead End	1/2"	ENR11152	ENR12152	ENR6152	6-15R	ENP6152	6-15P
			3/4"	ENR21152	ENR22152				
		Through Feed	1"	ENR31152	ENR32152				
			1/2"	ENRC11152	ENRC12152				
				3/4"	ENRC21152	ENRC22152			
				1"	ENRC31152	ENRC32152			
UL	20 A Receptacle Rating	Dead End	1/2"	ENR11201	ENR12201	ENR5201	5-20R	ENP5201	5-20P
			3/4"	ENR21201	ENR22201				
		Through Feed	1"	ENR31201	ENR32201				
			1/2"	ENRC11201	ENRC12201				
				3/4"	ENRC21201	ENRC22201			
				1"	ENRC31201	ENRC32201			
CSA	20 Amp 125 Volt	Dead End	1/2"	ENR11202	ENR12202	ENR6202	6-20R	ENP6202	6-20P
			3/4"	ENR21202	ENR22202				
		Through Feed	1"	ENR31202	ENR32202				
			1/2"	ENRC11202	ENRC12202				
				3/4"	ENRC21202	ENRC22202			
				1"	ENRC31202	ENRC32202			

†Receptacle units alone (i.e. ENR5201) are not suitable for Class I, Group B.

*Single gang assemblies purchased with an EDS back box are suitable for Class I, Group B.

**Dual gang assemblies purchased with an EDS back box are suitable for Class I, Group C, D only. For Class I, Group B rating, add the letter B to the Cat. No. Example: ENRB22201. Seals must be installed within 1/2" of each conduit opening.

‡ENP Plugs use #12 or #14 AWG type S, SO, ST or STO cord with range of .540 to .635 inches diameter.

Note: 15A with copper-free aluminum EDS, EDSC back boxes. 20A with Feraloy® iron alloy EDS, EDSC back boxes.

2P