

2P



# ENR Value Series Dead Front Interlocked Circuit Breaking Receptacles

## ENP Plugs

Cl. I, Div. 1 & 2, Groups B†, C, D  
 Cl. II, Div. 1 & 2, Groups F, G  
 Cl. III  
 NEMA 3, 7BCD, 9FG, 12

Explosionproof  
 Dust-Ignitionproof  
 Raintight  
 Wet Locations

### Ordering Information:

										
15 A	15 A Receptacle Rating	Description	Hub Size	Single Gang* Receptacle Assembly Cat. #	Two Gang** Receptacle Assembly Cat. #	Receptacle† Unit Only Cat. #	NEMA Config.	15 A Plug‡ Cat. #	NEMA Config.	
CSA	15 Amp 125 Volt	Dead End	1/2"	ENR11151	ENR12151	ENR5151	5-15R	ENP5151	5-15P	
			3/4"	ENR21151	ENR22151					
		Through Feed	1"	ENR31151	ENR32151					
			1/2"	ENRC11151	ENRC12151					
				3/4"	ENRC21151	ENRC22151				
				1"	ENRC31151	ENRC32151				
	15 Amp 250 Volt	Dead End	1/2"	ENR11152	ENR12152	ENR6152	6-15R	ENP6152	6-15P	
			3/4"	ENR21152	ENR22152					
		Through Feed	1"	ENR31152	ENR32152					
			1/2"	ENRC11152	ENRC12152					
				3/4"	ENRC21152	ENRC22152				
				1"	ENRC31152	ENRC32152				
UL	20 A	20 Amp 125 Volt	Dead End	1/2"	ENR11201	ENR12201	ENR5201	ENP5201	5-20P	
				3/4"	ENR21201	ENR22201				
		Through Feed	1"	ENR31201	ENR32201					
			1/2"	ENRC11201	ENRC12201					
				3/4"	ENRC21201	ENRC22201	5-20R			
				1"	ENRC31201	ENRC32201				
CSA	20 Amp 250 Volt	Dead End	1/2"	ENR11202	ENR12202	ENR6202	6-20R	ENP6202	6-20P	
			3/4"	ENR21202	ENR22202					
		Through Feed	1"	ENR31202	ENR32202					
			1/2"	ENRC11202	ENRC12202					
				3/4"	ENRC21202	ENRC22202				
				1"	ENRC31202	ENRC32202				

†Receptacle units alone (i.e. ENR5201) are not suitable for Class I, Group B.  
 \*Single gang assemblies purchased with an EDS back box are suitable for Class I, Group B.  
 \*\*Dual gang assemblies purchased with an EDS back box are suitable for Class I, Group C, D only. For Class I, Group B rating, add the letter B to the Cat. No. Example: ENRB22201. Seals must be installed within 1/2" of each conduit opening.  
 ‡ENP Plugs use #12 or #14 AWG type S, SO, ST or STO cord with range of .540 to .635 inches diameter.  
**Note:** 15A with copper-free aluminum EDS, EDSC back boxes. 20A with Feraloy® iron alloy EDS, EDSC back boxes.

2P