

2P




ENR Value Series Dead Front Interlocked Circuit Breaking Receptacles

ENP Plugs

Cl. I, Div. 1 & 2, Groups B†, C, D
 Cl. II, Div. 1 & 2, Groups F, G
 Cl. III
 NEMA 3, 7BCD, 9FG, 12

Explosionproof
 Dust-Ignitionproof
 Raintight
 Wet Locations

Ordering Information:

| | | | |  |  |  |  | | | |
|------|------------------------|-----------------|-----------|---|---|---|---|-------------------|--------------|-------|
| 15 A | 15 A Receptacle Rating | Description | Hub Size | Single Gang* Receptacle Assembly Cat. # | Two Gang** Receptacle Assembly Cat. # | Receptacle† Unit Only Cat. # | NEMA Config. | 15 A Plug‡ Cat. # | NEMA Config. | |
| CSA | 15 Amp 125 Volt | Dead End | 1/2" | ENR11151 | ENR12151 | ENR5151 | 5-15R | ENP5151 | 5-15P | |
| | | | 3/4" | ENR21151 | ENR22151 | | | | | |
| | Through Feed | 1" | ENR31151 | ENR32151 | | | | | | |
| | | 1/2" | ENRC11151 | ENRC12151 | | | | | | |
| | | 3/4" | ENRC21151 | ENRC22151 | | | | | | |
| | | 1" | ENRC31151 | ENRC32151 | | | | | | |
| UL | 15 Amp 250 Volt | Dead End | 1/2" | ENR11152 | ENR12152 | ENR6152 | 6-15R | ENP6152 | 6-15P | |
| | | | 3/4" | ENR21152 | ENR22152 | | | | | |
| | Through Feed | 1" | ENR31152 | ENR32152 | | | | | | |
| | | 1/2" | ENRC11152 | ENRC12152 | | | | | | |
| | | 3/4" | ENRC21152 | ENRC22152 | | | | | | |
| | | 1" | ENRC31152 | ENRC32152 | | | | | | |
| UL | 20 A Receptacle Rating | 20 Amp 125 Volt | Dead End | 1/2" | ENR11201 | ENR12201 | ENR5201 | 5-20R | ENP5201 | 5-20P |
| | | | | 3/4" | ENR21201 | ENR22201 | | | | |
| | Through Feed | 1" | ENR31201 | ENR32201 | | | | | | |
| | | 1/2" | ENRC11201 | ENRC12201 | | | | | | |
| | | 3/4" | ENRC21201 | ENRC22201 | | | | | | |
| | | 1" | ENRC31201 | ENRC32201 | | | | | | |
| CSA | 20 Amp 250 Volt | Dead End | 1/2" | ENR11202 | ENR12202 | ENR6202 | 6-20R | ENP6202 | 6-20P | |
| | | | 3/4" | ENR21202 | ENR22202 | | | | | |
| | Through Feed | 1" | ENR31202 | ENR32202 | | | | | | |
| | | 1/2" | ENRC11202 | ENRC12202 | | | | | | |
| | | 3/4" | ENRC21202 | ENRC22202 | | | | | | |
| | | 1" | ENRC31202 | ENRC32202 | | | | | | |

†Receptacle units alone (i.e. ENR5201) are not suitable for Class I, Group B.
 *Single gang assemblies purchased with an EDS back box are suitable for Class I, Group B.
 **Dual gang assemblies purchased with an EDS back box are suitable for Class I, Group C, D only. For Class I, Group B rating, add the letter B to the Cat. No. Example: ENRB22201. Seals must be installed within 1/2" of each conduit opening.
 ‡ENP Plugs use #12 or #14 AWG type S, SO, ST or STO cord with range of .540 to .635 inches diameter.
Note: 15A with copper-free aluminum EDS, EDSC back boxes. 20A with *Feraloy*® iron alloy EDS, EDSC back boxes.

2P