



Single-Phase—Main Lug Loadcenters

Single-Phase Three-Wire—120/240 Vac—Insulated/Bondable Split Neutral, continued

Main Ampere Rating	Maximum Number 1-Inch (25.4 mm)		Enclosure Type	Box Size	Wire Size Range Cu/Al 60°C or 75°C for Main Lugs	Loadcenter Catalog Number with Combination or NEMA Type 3R Cover ①			
	Spaces	Circuits							
BR1224L125 	125	12	12	Indoor	#6–2/0	BR1212L125 ②③④⑤			
		12	24	Indoor		BR1224L125 ②④⑤			
		12	24	Indoor		BR1224L125G ②④⑤			
		12	24	Indoor		BR1224L125DG ②④⑤⑥			
		12	24	Outdoor		BR1224L125R ②⑤⑦			
		16	16	Indoor		BR1616L125 ②④⑤			
		16	24	Indoor		BR1624L125 ②④			
		16	24	Indoor		BR1624L125G ②④			
		16	24	Outdoor		BR1624L125R ②⑦			
		20	20	Indoor		BR2020L125 ②④⑤			
		20	24	Indoor		BR2024L125 ②④			
		20	24	Indoor		BR2024L125G ②④⑤			
		20	24	Outdoor		BR2024L125R ②⑦			
		24	24	Indoor		BR2424L125 ②④			
		24	24	Indoor		BR2424L125G ②④⑤			
150	16	30	Indoor	C2	#1–300 kcmil	BR1630L150 ④⑥			
	20	30	Indoor			BR2030L150 ④⑥			
BR1224L200 	200	8	16	Outdoor	#1–300 kcmil	BR816L200RF ⑤⑦⑧			
		12	24	Indoor		BR1224L200 ④⑤⑥			
		12	24	Outdoor		BR1224L200R ⑤⑦⑧			
		20	40	Indoor		BR2040L200 ④⑥			
		20	40	Indoor		BR2040L200G ④⑤⑥			
		20	40	Outdoor		BR2040L200R ⑦⑧			
		24	40	Indoor		BR2440L200 ④⑥			
		30	40	Indoor		BR3040L200 ④⑥			
		30	40	Indoor		BR3040L200G ④⑤⑥			
		30	40	Outdoor		BR3040L200R ⑦⑧			
		40	40	Indoor		BR4040L200 ④⑥			
		40	40	Indoor		BR4040L200G ④⑥			
		40	40	Outdoor		BR4040L200R ⑦⑧			
		225	42	42		Indoor	L1	#1–300 kcmil	BR4242L225 ④
			42	42		Outdoor			BR4242L225R ⑦

Notes

- ① Ground bar kits priced separately unless otherwise noted. See **Page V1-T1-60**.
- ② Has notch for BREQS125 hold-down kit.
- ③ Single, movable neutral is provided.
- ④ Combination cover style.
- ⑤ Suitable for use as service equipment when not more than six main disconnecting means are provided and when not used as a lighting and appliance panelboard (see Article 408.34 of the NEC).
- ⑥ Ground bars GBK5 and GBK520 installed.
- ⑦ Rainproof panels are furnished with hub closure plates. For rainproof hubs, refer to **Page V1-T1-60**.
- ⑧ Ground bar GBK1220 installed.
- ⑨ Has notch for BRHDK125 hold-down kit.
- ⑩ Includes through-feed lugs for both phase and neutral conductors.