



Single-Phase—Main Lug Loadcenters

Single-Phase Three-Wire—120/240 Vac—Insulated/Bondable Split Neutral, continued

Main Ampere Rating	Maximum Number 1-Inch (25.4 mm)		Enclosure Type	Box Size	Wire Size Range Cu/Al 60°C or 75°C for Main Lugs	Loadcenter Catalog Number with Combination or NEMA Type 3R Cover ①			
	Spaces	Circuits							
BR1224L125 	125	12	12	Indoor	#6–2/0	BR1212L125 ②③④⑤			
		12	24	Indoor		B1	BR1224L125 ②④⑤		
		12	24	Indoor		B1	BR1224L125G ②④⑤		
		12	24	Indoor		B1	BR1224L125DG ②④⑤⑥		
		12	24	Outdoor		B1R	BR1224L125R ②⑤⑦		
		16	16	Indoor		B2	BR1616L125 ②④⑤		
		16	24	Indoor		B2	BR1624L125 ②④		
		16	24	Indoor		B2	BR1624L125G ②④		
		16	24	Outdoor		B2R	BR1624L125R ②⑦		
		20	20	Indoor		C1	BR2020L125 ②④⑤		
		20	24	Indoor		C1	BR2024L125 ②④		
		20	24	Indoor		C1	BR2024L125G ②④⑤		
		20	24	Outdoor		C1R	BR2024L125R ②⑦		
		24	24	Indoor		C2	BR2424L125 ②④		
		24	24	Indoor		C2	BR2424L125G ②④⑤		
150	16	30	Indoor	C2	#1–300 kcmil	BR1630L150 ④⑥			
	20	30	Indoor	C2		BR2030L150 ④⑥			
BR1224L200 	200	8	16	Outdoor	#1–300 kcmil	BR816L200RF ⑤⑦⑧			
		12	24	Indoor		B2	BR1224L200 ④⑤⑥		
		12	24	Outdoor		B2R	BR1224L200R ⑤⑦⑧		
		20	40	Indoor		C2	BR2040L200 ④⑥		
		20	40	Indoor		C2	BR2040L200G ④⑤⑥		
		20	40	Outdoor		C3R	BR2040L200R ⑦⑧		
		24	40	Indoor		C4	BR2440L200 ④⑥		
		30	40	Indoor		D1	BR3040L200 ④⑥		
		30	40	Indoor		D1	BR3040L200G ④⑤⑥		
		30	40	Outdoor		D1R	BR3040L200R ⑦⑧		
		40	40	Indoor		G1	BR4040L200 ④⑥		
		40	40	Indoor		G1	BR4040L200G ④⑥		
		40	40	Outdoor		G1R	BR4040L200R ⑦⑧		
		225	42	42		Indoor	L1	#1–300 kcmil	BR4242L225 ④
			42	42		Outdoor	L1R		BR4242L225R ⑦

Notes

- ① Ground bar kits priced separately unless otherwise noted. See Page V1-T1-60.
- ② Has notch for BREQS125 hold-down kit.
- ③ Single, movable neutral is provided.
- ④ Combination cover style.
- ⑤ Suitable for use as service equipment when not more than six main disconnecting means are provided and when not used as a lighting and appliance panelboard (see Article 408.34 of the NEC).
- ⑥ Ground bars GBK5 and GBK520 installed.
- ⑦ Rainproof panels are furnished with hub closure plates. For rainproof hubs, refer to Page V1-T1-60.
- ⑧ Ground bar GBK1220 installed.
- ⑨ Has notch for BRHDK125 hold-down kit.
- ⑩ Includes through-feed lugs for both phase and neutral conductors.