

Conduit Clips

Features

- Spring steel M Clips have finger closure
- Spring steel P Clips have push-in installation
- Helps to guide alignment with electrical box knockouts.
- 9/32" plain hole or 1/4"-20 thread impression options for mounting and field assembly to structure fasteners



Fig. #1

Patent Number: 5,533,696

Part Number	Fig. #	Conduit Size (in)	Mounting Hole (in)	Standard Packaging Quantity
6M*	1	For 14-2 thru 12-3 MC/AC and 3/8 Flexible Conduit	9/32 Plain	100
812M*	1	1/2 to 3/4	9/32 Plain	100
16M*	1	1	9/32 Plain	100
20M*	1	1 1/4	9/32 Plain	100
24M*	1	1 1/2	9/32 Plain	100
32M*	1	2	9/32 Plain	100
812M4I*	1	1/2 to 3/4	1/4-20 Thread Impression	100
6M4I*	1	For 14-2 thru 12-3 MC/AC and 3/8 Flexible Conduit	1/4-20 Thread Impression	100
16M4I*	1	1	1/4-20 Thread Impression	100
20M4I*	1	1 1/4	1/4-20 Thread Impression	100
24M4I*	1	1 1/2	1/4-20 Thread Impression	100
32M4I*	1	2	1/4-20 Thread Impression	100
8P†	2	1/2	9/32 Plain	100
12P†	2	3/4	9/32 Plain	100
16P†	2	1	9/32 Plain	100
8P4I†	2	1/2	1/4-20 Thread Impression	100
12P4I†	2	3/4	1/4-20 Thread Impression	100
16P4I†	2	1	1/4-20 Thread Impression	100

*M Series 100 lbs. Vertical • 25 lbs. Horizontal (static load)

†P Series 25 lbs. Vertical • 15 lbs. Horizontal (ultimate load)




Fig. #2

