







## FLIR ONE ANDROID FEATURES

- |  |  |   |
|--|--|---|
| <p><b>Radiometric</b></p> <p> FLIR ONE can measure temperatures on any spot in a scene between -4°F and 248°F (-20° to 120°C).</p>                        | <p><b>Warranty</b></p> <p> FLIR ONE's warranty covers defects in materials and workmanship for one year, or 18 months with registration.</p>  | <p><b>Palettes</b></p> <p> Select between seven dynamic video palettes, including B/W, W/B, rainbow, contrast, arctic, hot/cold, and iron.</p> |
| <p><b>Compatibility</b></p> <p> FLIR ONE attaches to any Android mobile device with a micro-USB port (<a href="#">See compatibility requirements</a>)</p> | <p><b>FLIR ONE App</b></p> <p> Explore additional features like FLIR ONE Panorama™, FLIR ONE TimeLapse™, and FLIR ONE CloseUp™ functions.</p> | <p><b>Sharing</b></p> <p> FLIR ONE App allows you to share thermal images and videos to the social media platform of your choice.</p>          |

## FLIR ONE FOR ANDROID SPECIFICATIONS

Model Number	FLIR ONE Android
Scene Temperature Range	-4°F to 248°F (-20° to 120°C)
Operating Temperature	32°F to 95°F (0°C to 35°C)
Weight	29 grams (~1oz)
Dimensions (L x W x H)	2.8 inches (72mm) x 1 inch (26mm) x 0.7 inches (18mm)
Battery Capacity	350 mA-h FLIR ONE neither consumes power from the connected device battery, nor charges it. When inactive, FLIR automatically switches to low-power mode to maximize its battery life.
Visible Camera	VGA (used for FLIR MSX blending)
Sensitivity	Ability to detect temperature differences as small as 0.18° F (0.1° C)
Charging Method	Micro-USB paired with 1A wall charger (charges FLIR ONE only, not device)
Certifications and Standards	FCC, CE, RoHS, CAN ICES-3 (B)/NMB-3(B), UL

*\*Disclaimer: Specifications are subject to change without notice. Availability of camera models and accessories subject to regional market considerations. Prices listed are US only, please consult your specific country for current pricing.*

## DEVICE COMPATIBILITY

To be compatible with FLIR ONE, a device must meet the minimum requirements and appear on the list below as a compatible device.

### Minimum Requirements:

- At least Android Version 4.4.2
- GPS, Location, OTG USB, Flashlight, and Microphone Capabilities
  - For Panorama functionality: Gyroscope and Accelerometer Capabilities
- GPS, Location, Microphone, and Flashlight Permissions