

# IEC Manual Motor Starters Selection Guide

## Section 6

### 45 mm Standard Interruption Capacity (Toggle Operator)

#### Individual or Group Installation, with or without C-2000 contactors or mini-contactors

FLA Adjustment Range	Three Phase Horsepower @ 200-208V	Three Phase Horsepower @ 220-240V	Three Phase Horsepower @ 440-480V	Three Phase Horsepower @ 575-600V	Single Phase Horsepower @ 115V	Single Phase Horsepower @ 230V	Instantaneous Short Circuit Release Amps	Product Number	List Price GO-10A2C
0.1-0.16							2.1	GPS1BSAA	\$88.00
0.16-0.25							3.3	GPS1BSAB	\$88.00
0.25-0.4							5.2	GPS1BSAC	\$88.00
0.4-0.63							8.2	GPS1BSAD	\$88.00
0.63-1.0			1/2	1/2			13	GPS1BSAE	\$100.00
1-1.6	1/4	1/3	3/4	3/4		1/10	20.8	GPS1BSAF	\$100.00
1.6-2.5	1/2	1/2	1	1 1/2		1/6	32.5	GPS1BSAG	\$100.00
2.5-4	3/4	3/4	2	3	1/8	1/3	52	GPS1BSAH	\$100.00
4-6.3	1	1 1/2	3	5	1/4	1/2	81.9	GPS1BSAJ	\$100.00
6.3-10	2	3	5	7 1/2	1/2	1 1/2	130	GPS1BSAK	\$100.00
9-13	3	3	7 1/2	10	1/2	2	169	GPS1BSAL	\$120.00
11-16	3	5	10	10	1	2	208	GPS1BSAM	\$120.00
14-20	5	5	10	15	1 1/2	3	260	GPS1BSAN	\$120.00
19-25	7 1/2	7 1/2	15	20	2	3	325	GPS1BSAP	\$135.00
24-32	10	10	20	30	2	5	416	GPS1BSAR	\$135.00

### 45 mm High Interruption Capacity (Rotary Operator)

#### Individual, Group or Combination<sup>1, 2</sup> Installation, with or without C-2000 contactors or mini-contactors

FLA Adjustment Range	Three Phase Horsepower @ 200-208V	Three Phase Horsepower @ 220-240V	Three Phase Horsepower @ 440-480V	Three Phase Horsepower @ 575-600V	Single Phase Horsepower @ 115V	Single Phase Horsepower @ 230V	Instantaneous Short Circuit Release Amps	Product Number	List Price GO-10A2C
0.1-0.16							2.1	GPS1BHAA	\$110.00
0.16-0.25							3.3	GPS1BHAB	\$110.00
0.25-0.4							5.2	GPS1BHAC	\$110.00
0.4-0.63							8.2	GPS1BHAD	\$110.00
0.63-1.0			1/2	1/2			13	GPS1BHAE	\$125.00
1-1.6	1/4	1/3	3/4	3/4		1/10	20.8	GPS1BHAF	\$125.00
1.6-2.5	1/2	1/2	1	1 1/2		1/6	32.5	GPS1BHAG	\$125.00
2.5-4	3/4	3/4	2	3	1/8	1/3	52	GPS1BHAH	\$125.00
4-6.3	1	1 1/2	3	5	1/4	1/2	81.9	GPS1BHAI	\$125.00
6.3-10	2	3	5	7 1/2	1/2	1 1/2	130	GPS1BHAK	\$125.00
9-13	3	3	7 1/2	10	1/2	2	169	GPS1BHAL	\$150.00
11-16	3	5	10	10	1	2	208	GPS1BHAM	\$150.00
14-20	5	5	10	15	1 1/2	3	260	GPS1BHAN	\$150.00
19-25	7 1/2	7 1/2	15	20	2	3	325	GPS1BHAP	\$165.00
24-32	10	10	20	30	2	5	416	GPS1BHAR	\$165.00

### 55 mm High Interruption Capacity (Rotary Operator)

#### Individual, Group or Combination<sup>2</sup> Installation, with or without C-2000 contactors or mini-contactors

FLA Adjustment Range	Three Phase Horsepower @ 200-208V	Three Phase Horsepower @ 220-240V	Three Phase Horsepower @ 440-480V	Three Phase Horsepower @ 575-600V	Single Phase Horsepower @ 115V	Single Phase Horsepower @ 230V	Instantaneous Short Circuit Release Amps	Product Number	List Price GO-10A2C
6.3-10	2	3	5	7 1/2	1/2	1 1/2	130	GPS2BHAK	\$245.00
9-13	3	3	7 1/2	10	1/2	2	169	GPS2BHAL	\$245.00
11-16	3	5	7 1/2	10	1	2	208	GPS2BHAM	\$245.00
14-20	5	5	10	15	1 1/2	2	260	GPS2BHAN	\$245.00
19-25	7 1/2	7 1/2	15	20	2	3	325	GPS2BHAP	\$245.00
24-32	10	10	20	25	2	5	416	GPS2BHAR	\$245.00
28-40	10	10	25	30	3	7 1/2	520	GPS2BHAS	\$275.00
35-50	15	15	30	40	3	10	650	GPS2BHAT	\$275.00
45-63	15	20	40	50	5	10	819	GPS2BHAU	\$302.00

<sup>1</sup>When using manual starters in combination starter applications, use short circuit reset/indicator accessory. For GPS1BH\_ starters add GPAPT1E terminal accessory.

<sup>2</sup>Maximum voltage for combination control is 277/480.

### Product Number Selection Instructions

Selection of the starter depends on the actual motor full load current and service factor. For motors with service factor of 1.15 or greater, use motor full load current to select the appropriate current range. For motors with a service factor less than 1.15, multiply the normal full load current by .9 for the current setting. Single phase applications require all three overload legs to be energized for proper operation. Use separate conductor to connect terminal T2 to L3. Connect power to L1 and L2 and apply load between T1 and T3.



# IEC Manual Motor Starters

## Short Circuit Current Rating

### Rated Breaking Capacity

## Section 6

### Toggle Operation, Standard Interruption

Product Number	FLA Adjustment Range	kAIC @ 240V	kAIC @ 480V	kAIC @ 600V	Max. Fuse Size (A)	Max. C.B. Size (A)	kAIC @ 240V-Group Installation	kAIC @ 480V-Group Installation	kAIC @ 600V-Group Installation	Max Fuse or C.B.-Size (A) Group Installation	Minimum Contactor Size
GPS1BSAA	0.1-0.16	100	50	10	0.75	15	100	65	25	500	CL00 or MCO
GPS1BSAB	0.16-0.25	100	50	10	1	15	100	65	25	500	CL00 or MCO
GPS1BSAC	0.25-0.4	100	50	10	1.5	15	100	65	25	500	CL00 or MCO
GPS1BSAD	0.4-0.63	100	50	10	2.5	15	100	65	25	500	CL00 or MCO
GPS1BSAE	0.63-1.0	100	50	10	4	15	100	65	25	500	CL00 or MCO
GPS1BSAF	1-1.6	100	50	10	6	15	100	65	25	500	CL00 or MCO
GPS1BSAG	1.6-2.5	100	50	10	10	15	100	65	25	500	CL00 or MCO
GPS1BSAH	2.5-4	100	50	10	16	15	100	65	25	500	CL00 or MCO
GPS1BSAJ	4-6.3	100	22	10	25	25	100	65	25	500	CL00 or MCO
GPS1BSAK	6.3-10	100	22	10	40	40	100	65	25	500	CL00 or MCO
GPS1BSAL	9-13	100	22	10	50	50	100	65	25	500	CL00
GPS1BSAM	11-16	65	22	10	60	60	65	50	18	500	CL01
GPS1BSAN	14-20	65	22	10	80	80	65	50	18	500	CL02
GPS1BSAP	19-25	65	22	10	100	100	65	50	18	500	CL25
GPS1BSAR	24-32	65	22	10	125	125	65	50	10	500	CL04

Manual motor starters are suitable for use with C-2000 contactors in series with the starter, but contactor rating must not be exceeded.

### Rotary Operation, High Interruption

Product Number	FLA Adjustment Range	kAIC @ 240V	kAIC @ 480V	kAIC @ 600V	Max. Fuse Size (A)	Max. C.B. Size (A)	kAIC @ 240V-Group Installation	kAIC @ 480V-Group Installation	kAIC @ 600V-Group Installation	Max Fuse or C.B. Size(A)-Group Installation	kAIC @ 277Y/480V-Combination Starter	Minimum Contactor Size
GPS1BHAA	0.1-0.16	100	50	10	0.75	15	100	65	25	500	50	CL00 or MCO
GPS1BHAB	0.16-0.25	100	50	10	1	15	100	65	25	500	50	CL00 or MCO
GPS1BHAC	0.25-0.4	100	50	10	1.5	15	100	65	25	500	50	CL00 or MCO
GPS1BHAD	0.4-0.63	100	50	10	2.5	15	100	65	25	500	50	CL00 or MCO
GPS1BHAE	0.63-1.0	100	50	10	4	15	100	65	25	500	50	CL00 or MCO
GPS1BHAF	1-1.6	100	50	10	6	15	100	65	25	500	50	CL00 or MCO
GPS1BHAG	1.6-2.5	100	50	10	10	15	100	65	25	500	50	CL00 or MCO
GPS1BHAH	2.5-4	100	50	10	16	15	100	65	25	500	50	CL00 or MCO
GPS1BHAJ	4-6.3	100	50	10	25	25	100	65	25	500	50	CL00 or MCO
GPS1BHAK	6.3-10	100	50	10	40	40	100	65	25	500	50	CL00 or MC1
GPS1BHAL	9-13	100	50	10	50	50	100	65	25	500	50	CL00
GPS1BHAM	11-16	65	50	10	60	60	65	65	25	500	50	CL01
GPS1BHAN	14-20	65	50	10	80	80	65	65	25	500	50	CL02
GPS1BHAP	19-25	65	50	10	100	100	65	65	25	500	50	CL25
GPS1BHAR	24-32	65	50	10	125	125	65	65	10	500	50	CL04
GPS2BHAK	6.3-10	65	50	10	40	40	100	65	25	1500	50	CL00
GPS2BHAL	9-13	65	50	10	50	50	100	65	25	1500	50	CL00
GPS2BHAM	11-16	65	50	10	60	60	100	65	25	1500	50	CL01
GPS2BHAN	14-20	65	50	10	80	80	100	65	25	1500	50	CL02
GPS2BHAP	19-25	65	50	10	100	100	100	65	25	1500	50	CL02
GPS2BHAR	24-32	65	50	10	125	125	100	65	25	1500	50	CL04
GPS2BHAS	28-40	65	50	10	150	150	100	65	10	1500	50	CL06
GPS2BHAT	35-50	65	50	10	200	200	100	65	10	1500	50	CL06
GPS2BHAU	45-63	65	50	10	250	250	100	35	10	1500	50	CL07

When using manual starters in combination with starter applications, use short circuit reset/indicator accessory. For GPS1BH\_ starters add GPAPTIE terminal accessory.

Maximum voltage for combination control is 277/480.

Manual motor starters are suitable for use with C-2000 contactors in series with the starter; contactor rating must not be exceeded. When used in a combination installation, the contactor is not self-protected.

Link available for GPS2\* for CL04 and larger contactors only.



# IEC Manual Motor Starters

## Type 2 Short Circuit Rating

### Individual Group and Combination Starters

#### Type 2 Coordination

Under short circuit conditions, the starter must not result in danger to persons or the installation. After short circuit, the starter shall be capable of further use. No damage to the overload relay or other parts shall occur, except that welding of the contactor contacts is permitted when they are easily separated (as by a screwdriver) without significant deformation. Minimum front electrical clearance is 1" with CL06 and CL07 contactors, 0.8" with all other contactors.

#### 100kA@240V UL508E Investigation (Individual Group or Combination)\*

Starter Type	FLA		Minimum Contactor Size	
	Adjustment Range	Product Number	@ 100kA @ 240V Interrupt Level	Link @ 100kA @ 240V Interrupt Level
GPS1	0.1-0.16	GPS1BHAA	CL00	GPF1L02*
GPS1	0.16-0.25	GPS1BHAB	CL00	GPF1L02*
GPS1	0.25-0.4	GPS1BHAC	CL00	GPF1L02*
GPS1	0.4-0.63	GPS1BHAD	CL00	GPF1L02*
GPS1	0.63-1.0	GPS1BHAE	CL00	GPF1L02*
GPS1	1-1.6	GPS1BHAF	CL00	GPF1L02*
GPS1	1.6-2.5	GPS1BHAG	CL00	GPF1L02*
GPS1	2.5-4	GPS1BHAH	CL00	GPF1L02*
GPS1	4-6.3	GPS1BHAJ	CL00	GPF1L02*
GPS1	6.3-10	GPS1BHAK	CL00	GPF1L02*
GPS1	9-13	GPS1BHAL	CL01	GPF1L02*
GPS1	11-16	GPS1BHAM	CL02	GPF1L02*
GPS1	14-20	GPS1BHAN	CL04	GPF1L04*
GPS1	19-25	GPS1BHAP	CL04	GPF1L04*
GPS1	24-32	GPS1BHAR	CL04	GPF1L04*
GPS2	6.3-10	GPS2BHAK	CL04	GPF2L04*
GPS2	9-13	GPS2BHAL	CL04	GPF2L04*
GPS2	11-16	GPS2BHAM	CL04	GPF2L04*
GPS2	14-20	GPS2BHAN	CL04	GPF2L04*
GPS2	19-25	GPS2BHAP	CL04	GPF2L04*
GPS2	24-32	GPS2BHAR	CL45	GPF2L45*
GPS2	28-40	GPS2BHAS	CL06	GPF2L07*
GPS2	35-50	GPS2BHAT	CL06	GPF2L07*
GPS2	45-63	GPS2BHAU	CL07	GPF2L07*

#### 50kA@380/400V per IEC947 (Individual Group or Combination)\*

Starter Type	FLA		Minimum Contactor Size	
	Adjustment Range	Product Number	@ 50kA @ 380/400V Interrupt Level	Link @ 50kA @ 380/400V Interrupt Level
GPS1	0.1-0.16	GPS1BHAA	CL00	GPF1L02*
GPS1	0.16-0.25	GPS1BHAB	CL00	GPF1L02*
GPS1	0.25-0.4	GPS1BHAC	CL00	GPF1L02*
GPS1	0.4-0.63	GPS1BHAD	LC00	GPF1L02*
GPS1	0.63-1.0	GPS1BHAE	CL00	GPF1L02*
GPS1	1-1.6	GPS1BHAF	CL00	GPF1L02*
GPS1	1.6-2.5	GPS1BHAG	CL01	GPF1L04*
GPS1	2.5-4	GPS1BHAH	CL01	GPF1L04*
GPS1	4-6.3	GPS1BHAJ	CL02	GPF1L04*
GPS1	6.3-10	GPS1BHAK	CL25	GPF1L25*
GPS1	9-13	GPS1BHAL	CL25	GPF1L25*
GPS1	11-16	GPS1BHAM	CL25	GPF1L25*
GPS1	14-20	GPS1BHAN	CL25	GPF1L25*
GPS1	19-25	GPS1BHAP	CL25	GPF1L25*
GPS1	24-32	GPS1BHAR	CL25	GPF1L25*
GPS2	6.3-10	GPS2BHAK	CL04	GPF2L04*
GPS2	9-13	GPS2BHAL	CL04	GPF2L04*
GPS2	11-16	GPS2BHAM	CL04	GPF2L04*
GPS2	14-20	GPS2BHAN	CL04	GPF2L04*
GPS2	19-25	GPS2BHAP	CL04	GPF2L04*
GPS2	24-32	GPS2BHAR	CL04	GPF2L04*
GPS2	28-40	GPS2BHAS	CL45	GPF2L45*
GPS2	35-50	GPS2BHAT	CL06	GPF2L07*
GPS2	45-63	GPS2BHAU	CL07	GPF2L07*

#### 50kA@480V UL508E Investigation (Individual Group or Combination)\*

Starter Type	FLA		Minimum Contactor Size	
	Adjustment Range	Product Number	@ 50kA @ 480V Interrupt Level	Link @ 50kA @ 480V Interrupt Level
GPS1	0.1-0.16	GPS1BHAA	CL01	GPF1L02*
GPS1	0.16-0.25	GPS1BHAB	CL01	GPF1L02*
GPS1	0.25-0.4	GPS1BHAC	CL01	GPF1L02*
GPS1	0.4-0.63	GPS1BHAD	CL01	GPF1L02*
GPS1	0.63-1.0	GPS1BHAE	CL01	GPF1L02*
GPS1	1-1.6	GPS1BHAF	CL01	GPF1L02*
GPS1	1.6-2.5	GPS1BHAG	CL25	GPF1L25*
GPS1	2.5-4	GPS1BHAH	CL25	GPF1L25*
GPS1	4-6.3	GPS1BHAJ	CL25	GPF1L25*
GPS1	6.3-10	GPS1BHAK	CL25	GPF1L25*
GPS1	9-13	GPS1BHAL	CL25	GPF1L25*
GPS1	11-16	GPS1BHAM	CL25	GPF1L25*
GPS1	14-20	GPS1BHAN	CL25	GPF1L25*
GPS1	19-25	GPS1BHAP	CL04	GPF1L04*
GPS1	24-32	GPS1BHAR	CL04 (35kA)	GPF1L04*
GPS2	6.3-10	GPS2BHAK	CL04	GPF2L04*
GPS2	9-13	GPS2BHAL	CL04	GPF2L04*
GPS2	11-16	GPS2BHAM	CL04	GPF2L04*
GPS2	14-20	GPS2BHAN	CL04	GPF2L04*
GPS2	19-25	GPS2BHAP	CL04	GPF2L04*
GPS2	24-32	GPS2BHAR	CL45	GPF2L45*
GPS2	28-40	GPS2BHAS	CL06	GPF2L07*
GPS2	35-50	GPS2BHAT	CL06	GPF2L07*
GPS2	45-63	GPS2BHAU	CL07	GPF2L07*

#### 25kA (or as noted) @600V UL508E Investigation (Individual Group or Combination)\*

Starter Type	FLA		Minimum Contactor Size	
	Adjustment Range	Product Number	@ 25kA @ 600V Interrupt Level	Link @ 25kA @ 600V Interrupt Level
GPS1	0.1-0.16	GPS1BHAA	CL00	GPF1L02*
GPS1	0.16-0.25	GPS1BHAB	CL00	GPF1L02*
GPS1	0.25-0.4	GPS1BHAC	CL00	GPF1L02*
GPS1	0.4-0.63	GPS1BHAD	CL00	GPF1L02*
GPS1	0.63-1.0	GPS1BHAE	CL00	GPF1L02*
GPS1	1-1.6	GPS1BHAF	CL00	GPF1L02*
GPS1	1.6-2.5	GPS1BHAG	CL04	GPF1L04*
GPS1	2.5-4	GPS1BHAH	CL04	GPF1L04*
GPS1	4-6.3	GPS1BHAJ	CL04	GPF1L04*
GPS1	6.3-10	GPS1BHAK	CL04	GPF1L04*
GPS1	9-13	GPS1BHAL	CL04	GPF1L04*
GPS1	11-16	GPS1BHAM	CL04	GPF1L04*
GPS1	14-20	GPS1BHAN	CL04	GPF1L04*
GPS1	19-25	GPS1BHAP	CL04	GPF1L04*
GPS1	24-32	GPS1BHAR	CL04	GPF1L04*
GPS2	6.3-10	GPS2BHAK	CL45 (5kA)	GPF2L45*
GPS2	9-13	GPS2BHAL	CL45 (5kA)	GPF2L45*
GPS2	11-16	GPS2BHAM	CL45 (5kA)	GPF2L45*
GPS2	14-20	GPS2BHAN	CL45 (5kA)	GPF2L45*
GPS2	19-25	GPS2BHAP	CL45 (5kA)	GPF2L45*
GPS2	24-32	GPS2BHAR	CL45 (5kA)	GPF2L45*
GPS2	28-40	GPS2BHAS	CL06 (10kA)	GPF2L07*
GPS2	35-50	GPS2BHAT	CL06 (10kA)	GPF2L07*
GPS2	45-63	GPS2BHAU	CL07 (10kA)	GPF2L07*

\*Maximum voltage for combination control 277/480. Minimum front electrical clearance is 1" with CL06 and CL07 contactors, and 0.8" with all other contactors.



## Starters

	GPS1	GPS2
<b>Protection</b>	Thermal and Magnetic	Thermal and Magnetic
<b>Maximum Rated Current I<sub>max</sub></b>	32A	63A
<b>Maximum Rated Operational Current I<sub>e</sub></b>	32A	63A
<b>Maximum Rated HP @ 460V</b>	20 Hp	40 hp
<b>Maximum Rated kW @ 400V</b>	15 kW	30kW
<b>Power Loss</b>	0.16-25A: 7 W 32A: 8.5 W	6.3-32A: 11W 40-50A: 15W 63A: 17W
<b>Width</b>	45 mm	55 mm
<b>Height</b>	90 mm	120 mm
<b>Depth</b>	75 mm (GPS1BS*)/ 92.5 mm (GPS1BH*)	107.5 mm
<b>No. of Poles</b>	3	3
<b>Operation</b>	Toggle (GPS1BS*)/ Rotary (GPS1BH*)	Rotary
<b>Mounting Position Turning to Front</b>	30°	30°
<b>Mounting Position Turning to Back</b>	90°	90°
<b>Mounting Position Turning to Side</b>	180°	180°
<b>DIN Rail Mounting</b>	Yes	Yes
<b>Mounting Screws</b>	2 M4 (#6 screws) with Optional Mounting Tab	Yes
<b>Operation Altitude</b>	Up to 2000 Meters (6500 Feet)	Up to 2000m (6500 ft)
<b>Storage Temperature</b>	-40 to +80° C (-40 to 176° F)	-40 to +80° C (-40 to 176° F)
<b>Operation Temperature</b>	-20 to +60° C (-4 to 140° F)	-20 to +60° C (-4 to 140° F)
<b>Temperature Compensation</b>	-20 to +60° C (-4 to 140° F)	-20 to +60° C (-4 to 140° F)
<b>Rated Insulation Voltage U<sub>i</sub></b>	690V	690V
<b>Rated Operation Voltage U<sub>e</sub></b>	690V	690V
<b>Rated Voltage U<sub>L</sub>, cUL</b>	600V	600V
<b>Rated Frequency</b>	50/60	50/60
<b>Rated Impulse Withstand Strength U<sub>imp</sub></b>	8KV	8KV
<b>Utilization Category IEC 60947-4-1</b>	AC3	AC3
<b>Overload Trip Class IEC 60947-4-1</b>	10	10
<b>Number of Current Ranges</b>	15	9
<b>Magnetic Release I<sub>e</sub> Max Setting</b>	13X	13X
<b>Shock Resistance to IEC60068-2-25</b>	30 g (width 20 ms)	30 g (width 20 ms)
<b>Vibration Resist., 50-150 Hz (X,Y,Z axis)</b>	5G	Contact factory
<b>Std DIN Rail Mtg</b>		
<b>Vib. Res., 50-150 Hz (X,Y,Z axis)</b>	8G	Contact factory
<b>DIN Rail Vib. Clamps</b>		
<b>Protection Degree (per IEC529)</b>	IP20 Safe from Finger Touch	IP20 Safe from Finger Touch
<b>Mechanical Performance</b>	100,000 ops (70,000 for 32 Amp)	50,000 ops
<b>Electrical Performance</b>	100,000 ops (70,000 for 32 Amp)	25,000 ops
<b>Max. Operation per Hour (Motor Start Up)</b>	25	25
<b>Phase Failure Protection</b>	Yes	Yes
<b>Trip Test Function</b>	Yes	Yes
<b>Trip Indication</b>	Yes	Yes
<b>Terminal Type</b>	Pozidrive 2/Slotted Comb.	Pozidrive 2/Slotted Comb.
<b>Max. Size Wire</b>		
1 Conductor w/o End Sleeve, solid or stranded	1-10 mm <sup>2</sup> /18-8 AWG	1-25 mm <sup>2</sup> /18-2 AWG stranded
2 Conductor w/o End Sleeve, solid or stranded	1-6 mm <sup>2</sup> /18-10 AWG	1-25 mm <sup>2</sup> /18-4 AWG stranded
1 Conductor w/ End Sleeve, stranded	1-6 mm <sup>2</sup> stranded	1-16 mm <sup>2</sup>
2 Conductor w/ End Sleeve, stranded	1-6 mm <sup>2</sup> stranded	1-16 mm <sup>2</sup>
<b>Torque</b>	2.0 Nm/18 lb. in.	4.0 Nm/36 lb. in.
<b>Standards</b>		
IEC 60947-1, 60947-2, 60947-4	Yes	Yes
Din VDE660T 100/101/102	Yes	Yes
UL 508/CSA 22.2	Yes	Yes
<b>Marking</b>		
CE	Yes	Yes
<b>Approvals</b>		
UL, cUL listed	Yes	Yes
<b>Shipping Approvals</b>	On Request	On Request
<b>PTB Test</b>	On Request	On Request

## Frontal Auxiliary Blocks

<b>UL Contact Rating per NEMA ICS3-125</b>	B300, Q300
<b>Continuous Ampere Rating</b>	5
<b>Rated Operation AC Voltage U<sub>e</sub></b>	115V, 230V
<b>Rated Operational AC Current I<sub>e</sub></b>	1.5A
<b>AC Utilization Category</b>	AC15
<b>Rated Operation DC Voltage U<sub>e</sub></b>	48V, 110V, 220V
<b>Rated Operational DC Current I<sub>e</sub></b>	1.38A, 0.55A, 0.27A
<b>DC Utilization Category</b>	DC13
<b>Terminal Type</b>	Pozidrive2/Slotted Comb.
<b>Max. Size Wire (75°C Cu wire only) 2 conductor</b>	0.5-2.5 mm <sup>2</sup> /18-14 AWG
<b>Torque</b>	0.8Nm/7 lb. in.

Frontal Mount with 1NO or 1NC Contact; Frontal Mount Alarm with 1NO or 1NC Contact.

## Lateral Auxiliary Blocks

<b>UL Contact Rating per NEMA ICS3-125</b>	A600, P300
<b>Rated Operation AC Voltage U<sub>e</sub></b>	125V, 230V, 400V, 500V, 690V
<b>Rated Operational AC Current I<sub>e</sub></b>	4A, 4A, 2.2A, 0.5A, 0.6A
<b>AC Utilization Category</b>	AC15
<b>Rated Operation DC Voltage U<sub>e</sub></b>	48V, 110V, 220V
<b>Rated Operational DC Current I<sub>e</sub></b>	5A, 1.3A, 0.5A
<b>DC Utilization Category</b>	DC13
<b>Terminal Type</b>	Pozidrive2/Slotted Comb.
<b>Max. Size Wire (75°C Cu wire only) 2 conductor</b>	0.5-2.5 mm <sup>2</sup> /18-14 AWG
<b>Torque</b>	0.8Nm/7 lb. in.
<b>Width</b>	Adds 9 mm

Lateral Mount Auxiliary with 2NO, 1NO+1NC or 2NC contacts; Lateral Mount Alarm/Auxiliary with 1NO+1NO, 1NO+1NC, 1NC+1NO, 1NC+1NC; Short Circuit Signal Contact 1NO+1NC (SPDT)

## Shunt Trip

<b>Power Consumption Pick-up (va/watts)</b>	21/12
<b>Power Consumption Tripping Voltage</b>	0.7-1.1 Ve
<b>Max. Operation Supply</b>	5 ms for DC coil
<b>Power Consumption Pick-Up Voltage</b>	0.85 - 1.1 Ve
<b>Max. Size Wire (75°C Cu wire only) 2 conductor</b>	0.5-2.5 mm <sup>2</sup> /18-14 AWG
<b>Torque</b>	0.8Nm/7 lb. in.
<b>Width</b>	Adds 18 mm

## Undervoltage Release

<b>Power Consumption Pick-up (va/watts)</b>	21/12
<b>Power Consumption Holding (va/watts)</b>	8/1.2
<b>Power Consumption Tripping Voltage</b>	0.35-0.7 Ve
<b>Power Consumption Pick-Up Voltage</b>	0.85-1.1 Ve
<b>Torque</b>	0.8Nm/7 lb. in.
<b>Max. Size Wire (75°C Cu wire only) 2 conductor</b>	0.5-2.5 mm <sup>2</sup> /18-14 AWG
<b>Width</b>	Adds 18 mm

