

## Kellems® Wire Management Products

**PG and Metric Threaded Deluxe Cord Grips**

Aluminum Fittings, Stainless Steel Mesh, Liquidtight, for Insulated Cables

**WARNING!**

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-71 through T-76.



Straight PG Male



Straight Metric Male

**Straight PG\* Male Thread**

Cord Diameter Range		Hub Size	Catalog Numbers
Inches	(cm)		
.500"-.625"	(1.27-1.59)	PG16	074PG16010
.500"-.625"	(1.27-1.59)	PG21	074PG21010
.625"-.750"	(1.59-1.90)	PG21	074PG211247
.750"-.875"	(1.90-2.22)	PG21	074PG211248
.625"-.750"	(1.59-1.90)	PG29	074PG29021
.750"-.875"	(1.90-2.22)	PG29	074PG29023
.875"-1.000"	(2.22-2.54)	PG29	074PG29025
1.125"-1.250"	(2.86-3.17)	PG29	074PG291028**
1.125"-1.250"	(2.86-3.17)	PG36	074PG36028**

\* Panzergewinde

\*\*Cable jacket may have to be stripped to pass through connector body.

**Straight Metric Male Thread**

Cord Diameter Range		Form Size	Catalog Numbers
Inches	(cm)		
.500"-.625"	(1.27-1.59)	F2	074M20010
.625"-.750"	(1.59-1.90)	F3	074M251247
.750"-.875"	(1.90-2.22)	F3	074M251248
.625"-.750"	(1.59-1.90)	F2	074M25017
.750"-.875"	(1.90-2.22)	F4	074M32021
.875"-1.000"	(2.22-2.54)	F4	074M32023
1.125"-1.250"	(2.86-3.17)	F4	074M32025
1.125"-1.250"	(2.86-3.17)	F5	074M321028
1.125"-1.250"	(2.86-3.17)	F5	074M321250

**Specifications**

Material	Temperature Range
Aluminum	-30°F to +240°F (-34°C to +115°C).
Stainless Steel (Gotcha Rings)	-30°F to +240°F (-34°C to +115°C).
Neoprene (Bushings)	-30°F to +240°F (-34°C to +115°C).

**Hazardous Locations** Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C. Reference 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).

**Approvals**

Cord Connectors	UL Listed in accordance with Standard 514B.
Deluxe Cord Grips	UL Control numbers 898D and 899D.

**Wet Locations**

Suitable for use in wet locations when used with a listed nylon washer between box and fitting.

When used with a metal clad o-ring, product has UL 4X environmental rating.

Note: \*Cable jacket may have to be stripped to pass through connector body. Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).