

INSULATED MECHANICAL

Aluminum Black Pre-Insulated Power Bars Double-Sided Conductor Entry

Type IPBB-D

Manufactured from high strength aluminum alloy

Dual rated for aluminum and copper conductors, 600 Volt, 90°C

Wide conductor range: 750 kcmil - 14 Sol.

- Allows flexibility in the field and reduces number of connectors in inventory

Multiple conductor configurations: 2 through 14 position

- Choose the right connector for the application

Double sided configuration allows conductors to be installed from either side of connector


Suitable for use in panelboards, cable trays, raceways, ducts and troughs

Pre-filled with oxide inhibitor, prevents oxidation, moisture and contaminants from entering contact area

Supplied with removable access plugs over screw and conductor ports providing protection against contaminants

Pre-insulated at factory with black high dielectric strength plastisol

- Black insulation is UV resistant
- Saves time, eliminates taping, reduces overall installation costs
- Abrasion and chemical resistant
- Will not support combustion



DOUBLE SIDED ENTRY

CATALOG NUMBER	NUMBER OF CONDUCTORS	CONDUCTOR RANGE	APPROXIMATE DIMENSIONS (IN.)			HEX SIZE		
			L	W	H			
IPBB-NA4-2D	2	4 Str. - 14 Sol.	1.39	1.50	1.25	1/8		
IPBB-NA4-3D	3		1.99	1.50	1.25			
IPBB-NA4-4D	4		2.59	1.50	1.25			
IPBB-NA4-5D	5		3.19	1.50	1.25			
IPBB-NA4-6D	6		3.79	1.50	1.25			
IPBB-NA4-8D	8		4.99	1.50	1.25			
IPBB-NA4-10D	10		6.19	1.50	1.25			
IPBB-NA4-12D	12		7.39	1.50	1.25			
IPBB-NA4-14D	14		8.59	1.50	1.25			
IPBB-NA2/0-2D	2		2/0 Str. - 14 Sol.	1.64	1.56		1.38	3/16
IPBB-NA2/0-3D	3			2.37	1.56		1.38	
IPBB-NA2/0-4D	4			3.09	1.56		1.38	
IPBB-NA2/0-5D	5			3.82	1.56		1.38	
IPBB-NA2/0-6D	6			4.54	1.56		1.38	
IPBB-NA2/0-8D	8	5.99		1.56	1.38			
IPBB-NA2/0-10D	10	7.44		1.56	1.38			
IPBB-NA2/0-12D	12	8.89		1.56	1.38			
IPBB-NA2/0-14D	14	10.34		1.56	1.38			

Type IPBB-D (continued)

CATALOG NUMBER	NUMBER OF CONDUCTORS	CONDUCTOR RANGE	APPROXIMATE DIMENSIONS (IN.)			HEX SIZE
			L	W	H	
IPBB-NA250-2D	2	250 kcmil - 10 Sol.	2.15	2.63	2.13	5/16
IPBB-NA250-3D	3		3.15	2.63	2.13	
IPBB-NA250-4D	4		4.15	2.63	2.13	
IPBB-NA250-5D	5		5.15	2.63	2.13	
IPBB-NA250-6D	6		6.15	2.63	2.13	
IPBB-NA250-8D	8		8.15	2.63	2.13	
IPBB-NA250-10D	10		10.15	2.63	2.13	
IPBB-NA250-12D	12		12.15	2.63	2.13	
IPBB-NA250-14D	14		14.15	2.63	2.13	
IPBB-NA350-2D	2	350 kcmil - 10 Sol.	2.40	3.00	2.50	5/16
IPBB-NA350-3D	3		3.53	3.00	2.50	
IPBB-NA350-4D	4		4.65	3.00	2.50	
IPBB-NA350-5D	5		5.78	3.00	2.50	
IPBB-NA350-6D	6		6.90	3.00	2.50	
IPBB-NA350-8D	8		9.15	3.00	2.50	
IPBB-NA350-10D	10		11.40	3.00	2.50	
IPBB-NA350-12D	12		13.65	3.00	2.50	
IPBB-NA350-14D	14		15.90	3.00	2.50	
IPBB-NA600-2D	2	600 kcmil - 4 Str.	2.80	3.00	2.75	3/8
IPBB-NA600-3D	3		4.13	3.00	2.75	
IPBB-NA600-4D	4		5.45	3.00	2.75	
IPBB-NA600-5D	5		6.78	3.00	2.75	
IPBB-NA600-6D	6		8.10	3.00	2.75	
IPBB-NA600-8D	8		10.75	3.00	2.75	
IPBB-NA600-10D	10		13.40	3.00	2.75	
IPBB-NA600-12D	12		16.05	3.00	2.75	
IPBB-NA600-14D	14		18.70	3.00	2.75	
IPBB-NA750-2D	2	750 kcmil - 2 Str.	3.02	3.38	3.00	3/8
IPBB-NA750-3D	3		4.46	3.38	3.00	
IPBB-NA750-4D	4		5.89	3.38	3.00	
IPBB-NA750-5D	5		7.33	3.38	3.00	
IPBB-NA750-6D	6		8.76	3.38	3.00	
IPBB-NA750-8D	8		11.63	3.38	3.00	
IPBB-NA750-10D	10		14.50	3.38	3.00	
IPBB-NA750-12D	12		17.37	3.38	3.00	
IPBB-NA750-14D	14		20.24	3.38	3.00	