



Silicone Coated PS

Sil Ctd 200W Med 120V PS30 FR-Sil 1CT

The Philips Family of Silicone Coated PS bulbs are the perfect choice in areas where there is concern if a bulb drops or shatters. Since Silicone Coated PS bulbs resist breakage or shattering, they are perfect for food serving areas, as well as, standard, industrial rough surface, appliance and sign use.

Product data

• General Characteristics

Base	Medium [Single Contact Medium Screw]
Base Information	Aluminum [Aluminum Base]
Bulb	PS30
Bulb Finish	Frost Silicone
Filament Shape	C-9 [Pendant]
Operating Position	Universal [Any or Universal (U)]
Main Application	Silicon Coated
Atmosphere	Gas

• Electrical Characteristics

Watts	200 W
Voltage	120 V

• Product Dimensions

Max Overall Length (MOL) - C	8.063 (max) in
------------------------------	----------------


• Footnotes

Footnotes Incandescent	66 [Silicone Coating reduces lumen output from Standard Values less than 3%. (66)]
------------------------	--


• Product Data

Product number	142983
Full product name	Sil Ctd 200W Med 120V PS30 FR-Sil 1CT
Short product name	Sil Ctd 200W Med 120V PS30 FR-Sil 1CT
Pieces per Sku	1
eop_pck_cfg	60
Skus/Case	60
Bar code on pack	46677142988
Bar code on case	50046677142983
Logistics code(s)	925266736302
eop_net_weight_pp	0.001 kg

Dimensional drawing



E26, PS30



E26, PS30



E26



© 2012 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2012, August 4
data subject to change