



480V 5% Impedance - Encapsulated  
240 Volts 10% Z - 480 Volts 5% Z - 600 Volts 4% Z  
AC Line Reactor - Three Phase - Encapsulated

1154



Catalog #: ALRC025LWE

**PRODUCT FEATURES**

- Indoor or Outdoor Applications
- Can be used with 208V, 240V, 480V, and 600V
- Gapped iron core with precision wound copper coils
- Compact design for more flexible installation
- Covered under Acme's 10 year limited warranty

**BENEFITS**

- Protects from damaging voltage drop
- Eliminates nuisance tripping
- Reduces surges and spike currents
- Longer life for motors and solid state components

**UL STANDARD**

UL 506

**CSA STANDARD**

C22.2 No 66

**GENERAL PRODUCT INFORMATION**

Primary Voltage:	240V / 480V / 600V
Frequency:	60 Hz
Impedance:	10% / 5% / 4%
Motor HP:	15
Motor Current:	21 A
Reactor Current:	25 A
Inductance:	1470 uH
Max Temperature Rise:	115°C
UL Insulation Class:	180°C

**PRODUCT MEASUREMENTS**

Height (In./cm):	11.50 (29.2)
Width (In./cm):	10.31 (26.2)
Depth (In./cm):	7.13 (18.1)

**PACKAGING**

Ship Weight (Lbs/Kg):	32 (14.5)
-----------------------	-----------

**COMPLIANCES**

UL Standard:	UL 506
UL Listed:	File E79947
CSA Standard:	C22.2 No 66
CSA Listed:	LR7357-16

