

Example of the parts to order to build a complete GS or LK switch:

Choose a Switch

+

Shaft

+

Handle Assembly

+

Lugs if needed



600 A, LK4SU3N



Shaft 320 mm, GS2AE6



Black Handle, GS2AH150



Lugs Kit, GS1AW503

Example:

LK4SU3N (600 A nonfusible switch, use 15x12 shaft) + GS2AE6 (320 mm Type S shaft) + GS2AH150 (black/ black, lockable)

To add auxiliary contacts:

For front-mounted contacts order LK4AD30N (front-mounted auxiliary contact holder) + GS2AM110.



30-60 A Compact



100-400 A



GS2AH130



GS2AH150



GS2AH170

Table 8.26: LK Nonfusible IEC Style Disconnect Switches

Pole	Rating (A)	Catalog Number	\$ Price	Maximum Horsepower Rating				Short Circuit Current Rating 600 Vac	
				240 V	480 V	600 V	250 Vdc	Fuse	SCCR kA
			218.00				—	J	100
3	60	LK4GU3CN	263.00			50	—	J	100
3	100	LK4JU3N		30	75	100	15	J	200
3	200	LK4MU3N		75	150	200	15	J	200
3	400	LK4OU3N	1910.00	125	250	350	50	J	200
3	600	LK4SU3N	2873.00						
		LK4TU3N		200	500	500	—	L	100
3	1000	LK4U3N		200	500	500	—	L	100
3	1200	LK4WU3N		200	500	500	—	L	100

Table 8.27: Handles and Shafts for LK Switches

Rating (A)	Handle				Shaft: 12.8/320 in./mm		Shaft: 15.7/400 in./mm		Shaft Guide	
	Catalog Number	Type	Color	\$ Price	Catalog Number	\$ Price	Catalog Number	\$ Price	Catalog Number	\$ Price
	LK4AH110CN	1, 3R, 12	Black							
30-60	LK4AH120CN	1, 3R, 12	Red/Yellow		LK4AE12CN		—	—	LK4AEAH12CN	15.50
30-60	LK4AH410CN	4, 4X	Black							
30-60	LK4AH420CN	4, 4X	Red/Yellow							
100-400	GS2AH130	1, 3R, 12	Black							
100-400	GS2AH140	1, 3R, 12	Red/Yellow							
100-400	GS2AH430	4, 4X	Black		GS2AE2		GS2AE21			
100-400	GS2AH440	4, 4X	Red/Yellow							
600	GS2AH150	4, 4X	Black							
600	GS2AH160	4, 4X	Red/Yellow							
800-1200	GS2AH170	4, 4X	Black		GS2AE6		GS2AE61			
800-1200	GS2AH180	4, 4X	Red/Yellow							

▲ Required on shafts for LK4DU3CN and LK4GU3CN switches.

Auxiliary Contacts for LK Switches

Switch Amperes	Catalog Number	Description	\$ Price
		Aux Contact 1 N.O. and 1 N.C.	
30-60	MDSAN20	Aux Contact 2 N.O. and 2 N.C.	
100-400	LK4AD10N	Aux Contact 1 N.O. and 1 N.C.	
100-400	LK4AD20N	Aux Contact 2 N.O. and 2 N.C.	
600-1200	LK4AD30N	Aux Contact Holder	
600-1200	GS2AM110	Aux Contact 1 N.O.	
600-1200	GS2AM101	Aux Contact 1 N.C.	

Switch Amperes	Catalog Number	Description	\$ Price
30-60	LK4AP3CN	Shroud Top and Bottom, 3-Pole	
100-200	LK4AP33TN	Shroud Top LK4, 3-Pole, 100/200 A	
100-200	LK4AP33BN	Shroud Bottom LK4, 3-Pole, 100/200 A	
400	LK4AP53TN	Shroud Top LK4, 3-Pole, 400 A	
400	LK4AP53BN	Shroud Bottom LK4, 3-Pole, 400 A	
600			

600-1200 A standard with top shroud.