



Testing & Measurement



TEMPERATURE

TG-600 Infrared Thermometer



- Safe, non-contact temperature measurement.
- Laser indicates approximate center of the target area.
- Displays temperatures in either Fahrenheit or Celsius.
- Auto power off for longer battery life.
- Easy-to-read backlit display for use in low light conditions.
- Accessories included: (1) 9V battery and carrying case.
- Lifetime Limited Warranty

CAT. NO.	UPC NO.	DESCRIPTION
TG-600	09031	Infrared Thermometer

SPECIFICATIONS	
Optical Resolution	12:1 at focus point
Target Temperature Range:	-4°F to 932°F (-20°C to 500°C)
Accuracy:	±2% or 4°F (±2°C)
Repeatability:	Within ±1% of reading or ±2°F (1°C)
Response Time:	500 ms, 95% response
Emissivity:	Preset at 0.98

<small>AVOID EXPOSURE - LASER RADIATION IS EMITTED FROM THIS APERTURE.</small> 	CAUTION	<small>COMPLIES WITH FDA 21 CFR SUBCHAPTER J</small>
	<small>LASER RADIATION - SEE NOTE 2 (PAGE 207) BEHIND OUTPUT - 1.1 MW WAVELENGTH 650-670 nm CLASS II LASER PRODUCT</small>	

THH-100 Infrared Thermometer



- Safe, non-contact temperature measurement of terminals, lugs, motors and circuit breakers.
- Accurate, easy laser targeting makes it quick and easy to aim precisely.
- Convenient display hold.
- Reads in either Celsius or Fahrenheit.
- Accessories included: (2) 1.5V AAA batteries and carrying case.
- Lifetime Limited Warranty

CAT. NO.	UPC NO.	DESCRIPTION
THH-100	09030	Handheld Infrared Thermometer

SPECIFICATIONS	
Target Temperature Range:	0°F-600°F (-18°C to 315°C)
Accuracy:	±2.5% of reading or ±5°F (±2.5°C), whichever is greater
Repeatability:	±1% of reading or ±2°F (±1°C), whichever is greater.
Response Time:	500ms, 95% response
Spectral Response:	7-14
Emissivity:	Fixed at 0.95
Optics:	6:1

<small>AVOID EXPOSURE - LASER RADIATION IS EMITTED FROM THIS APERTURE.</small> 	CAUTION	<small>COMPLIES WITH FDA 21 CFR SUBCHAPTER J</small>
	<small>LASER RADIATION - SEE NOTE 2 (PAGE 207) BEHIND OUTPUT - 1.1 MW WAVELENGTH 650-670 nm CLASS II LASER PRODUCT</small>	

International Tel: +1.815.397.7070
Fax: +1.815.397.9247

Canada Tel: 800.435.0786
Fax: 800.524.2853

USA Tel: 800.435.0786
Fax: 800.451.2632

(R) = REPLACEMENT PART (A) = ACCESSORY