

Russellstoll[®]

Russellstoll Control Circuit Connector

T&B Catalog Number:

SKWR10G

UPC Number:

70891713798

Status:

Active

Description:

Watertight Receptacle, 9 Pole 10 Wire

IMAGE NEEDED

Features

Watertight and oil tight

Generous Wiring Space

Ground contacts "make first" and "break last."

Application

Designed for outdoor NEMA 4, rough service and critical environment machinery, HVACR systems, servo control and other automatic/controlled functions requiring rugged, shock-resistant devices capable of safely breaking rated loads.

Automotive/Industrial Interlock systems were designed for the needs of the manufacturing industry. These devices are used where safety requirements mandate a mechanically interlocked system for connecting and removal of plugs under full load.

Designed for outdoor NEMA 4, rough service and critical environment machinery, HVACR systems, servo control and other automatic/controlled functions requiring rugged, shock-resistant devices capable of safely breaking rated loads.



General

Style	Watertight Receptacle
Material	Receptacle housing made of cast aluminum, corrosion-resistant, copper-free alloy.
Material_1	Furnished with Neoprene gasket and stainless steel 6- 32 mounting screws.
Frequency	60 Hz
Amperage	20 Amp
Pole/Wire	9P/10W
System	Control Circuit & Industrial Interlock

Specifications

NEMA Rating	4
Voltage	600 Volts AC (Maximum Rating)/250 Volts DC

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	1.2 lbs. Each

Application Support

Overview	Available on Website
Russellstoll Application Guide	Available on Website

Notes

Plugs and connectors can be furnished with adapters to accommodate rigid conduit or standard connectors for armored and non-metallic cable or flexible conduit.

Certifications

RoHS Compliance	No
-----------------	----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com